

Refresh Bar Unparalleled versatility



ERICA

Unparalleled versatility

Refresh Bar is the only range of coolers that can be located both under the sink and on the counter, thus fulfilling any future needs. The connections for the taps are provided on both sides so that, at any time, the cooler can be used lengthwise or depthwise to suit requirements.

Unparalleled for hygiene levels and ease of cleaning

Refresh Bar has a stainless steel ice bucket. All of the parts it contains, including the cooling coil and carbonator (found in the GPLUS 20 and GPLUS 32 models) can be removed for easier maintenance and cleaning.

Unparalleled standard features

Refresh Bar offers water recirculation as standard so that the dispensing column can be positioned up to 5 meters away, in the case of a height difference, and a good 10 metres away if the surface is horizontal. The robust frame and practical professional drip tray, both stainless steel, are also provided as standard.

No temperature problems

Called the Sahara Clima, the specially designed Zerica system allows this cooler to function perfectly even in extreme temperature conditions of up to 43°C.

Easy maintenance

All of the ordinary maintenance operations are easy so can be carried out at the user's premises without interruptions to service.

Four models for a tailor-made solution

Refresh Bar C20 and C32 differ with regard to the amount of cold and ambient water that they can dispense. The G Plus series models dispense the same amount of cold water as their C series counterparts with the added bonus of having a professional carbonator to produce sparkling water. Designed to enable long, continuous dispensing of sparkling water regardless of the size of the CO₂ mixing chamber.

STANDARD ACCESSORIES

- recirculation to cool the pipes with taps located remotely
- stainless steel cabinet
- 2-dial professional stainless steel carbonator with CO₂ reducer
- (modd. GPLUS 20 e GPLUS 32)
- stainless steel drip tray (Mods. GPLUS)


OPTIONAL ACCESSORIES

- 2-or 3- tap connector kit for use as undersink unit
- dispensing column connection kit - 2-or 3-way dispensing column
- CO₂ bottle
- head for filter cartridge
- filter cartridge
- kit for connection to a cooler bottle to be independent of mains water



GPLUS 20-32

	C20	C32	GPLUS 20	GPLUS 32
COUNTER/UNDERSINK POSITION	BOTH	BOTH	BOTH	BOTH
DISPENSES COLD AND AMBIENT WATER	✓	✓	✓	✓
DISPENSES SPARKLING WATER	-	-	✓	✓
COOLING SYSTEM	DIRECT CHILL	DIRECT CHILL	DIRECT CHILL	DIRECT CHILL
* COOLING CAPACITY (Δt=4°C/ Δt=14°C)	63/18 l/h	113/32 l/h	63/18 l/h	113/32 l/h
* ICE BANK DISP. (Δt=4°C/ Δt=14°C)	80/23 LITRES	88/25 LITRES	80/23 LITRES	88/25 LITRES
COOLING TANK CAPACITY	12 LITRES	12 LITRES	12 LITRES	12 LITRES
RECIRCULATING PUMP	✓	✓	✓	✓
STAINLESS STEEL ICE BANK	✓	✓	✓	✓
STAINLESS STEEL CABINET	✓	✓	✓	✓
DRIP TRAY	OPTIONAL	OPTIONAL	✓	✓
COMPRESSOR POWER	1/6 HP	1/3 HP PLUS	1/6 HP	1/3 HP PLUS
COLD WATER THERMOSTAT	✓	✓	✓	✓
** AMPERE	1,2	3	3	5
NET WEIGHT (GROSS) - kg	27 (28)	37 (38)	28 (29)	38 (39)
DIMENSIONS (HxWxD) - cm	43 x 34 x 50	51 x 34 x 50	43 x 34 x 50	51 x 34 x 50



Tap connections are provided on both sides to enable users to optimise the available space

- NOT AVAILABLE ✓ STANDARD *THE VALUES SHOWN MAY VARY DEPENDING ON THE ENVIRONMENT AND USE OF THE PRODUCT. **VALUES REFER TO 230 V 50Hz - 20°C (± 10%)



Zerica - Zona Industriale 90018 Termini Imerese (PA) Italy
tel. +39.091.8140341 PBX - www.zerica.com - info@zerica.com

ZERICA, REFRESH and HPDC are registered trademarks of Zerica srl Italia, which reserves the right to make any changes without notice