



ROSMO 400 GPD

Direct flow Reverse Osmosis with build in storage tank

Rosmo 400GPD water purifiers are sleek in design and compact in size, making it easy to fit in your home or business without taking too much space under your counter. It provides you, your family and your company with the highest quality of water directly to your tap! No need for carrying water bottles, with microplastic pollutants. By switching to Rosmo 400GPD you are helping to protect the environment by reducing the use of plastic water bottles.

- Rosmo 400GPD purifies your mains incoming water by removing 99.9% of any impurities that can be found in typical tap water
- Powered by cutting edge Filtration System, Rosmo 400GPD is fitted with four water filters and selective membrane
- Clean and healthy water at your desired TDS Total Dissolved Solids
- Water on demand technology. The Rosmo 400GPD starts producing water when you need it at a constant flow
- Compact size for better aesthetics and space saving
- Low operating noise level comparing with other models
- Touch panel with filter life reset
- Lifetime of filters display and reminder
- Automatic energy saving function with light sensor
- Optional UV lamp for effective sterilization against bacteria
- Optional 2 different water qualities output
- Optional mineral enrichment filter
- Optional bacteriostatic filters
- Optional Storage tank compatibility
- Replacement of filters in less than 30 minutes
- When the device is out of order it can save the settings, you have set for 1 week
- NSF Certified Filters

General Information	ROSMO 400GPD Direct Flow
Classification	Direct Flow 400G Selective
Color	Black
Features	Stainless faucet, build in storage tank, cartridge lifetime sensors, incoming and outgoing TDS sensors, working temperature, working modes, leakage safety system
Water Flow	From 1.2L/min
Build In tank capacity	1.0L
Purification System Steps	1st : PP Sediment Filter 5mic 2 nd : Carbon Block Filter 5 mic 3 rd : Membrane 400GPD 4 th : Inline Postfilter Cartridge
Voltage	(220-240V 、 50Hz) 24V 2.5A
TDS Control	Outlet TDS control
System Net Size	16(W) * 43(L) * 39(H) cm
Package Size	23(W) * 53(L) * 47(H) cm